

IND80

EM / INDUSTRIAL TYRES

IND80	Product Code	Tire Size & Ply Rating	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth	TRA Code	Load & Pressure		Dynamic Rolling Circumference	Static Loaded Radius
				Section Width	Overall Diameter					Tire Load Capacity	Tire Pressure At Max. Load		
				in	in			lbs		Psi			
	1946161242	10-16.5 12PR	TL	10.1	31.2	138	A3	19	R-4	5200	84	93.5	14.1
	1946162252	12-16.5 14PR	TL	11.7	33.8	148	A3	21	R-4	6950	90	100.7	15.1
	1946181042	10.5/80-18 12PR	TL	10.7	35.1	135	A8	23	R-4	4800	62	105.0	15.9
	1946182152	12.5/80-18 14PR	TL	11.2	37.6	146	A8	30	R-4	6600	62	112.0	16.9
	1946207062	16.0/70-20 16PR	TL	15.2	43.0	166	A2	33	R-4	11700	65	127.7	19.2
	1946243062	15.5/80-24 16PR	TL	16.2	50.0	162	A8	40	R-4	10500	72	148.8	22.4
	1946245062	16.0/70-24 16PR	TL	16.5	47.2	169	A2	35	R-4	12800	65	141.1	21.3
	1946246062	16.9-24 16PR	TL	16.9	51.6	154	A8	34	R-4	8250	46	153.3	23.0
	1946247052	17.5L-24 14PR	TL	18.7	50.3	154	A8	29	R-4	8250	46	149.7	22.5
	1946248052	19.5L-24 14PR	TL	19.5	51.7	154	A8	33	R-4	8250	38	153.8	23.1
	1946251052	15.5-25 14PR	TL	15.7	50.6	173	A2	29	L-2/G-2	14300	68	151.0	22.8
	1946261052	18.4-26 14PR	TL	18.4	56.1	160	A8	32	R-4	9900	42	166.8	25.0
	1946281052	16.9-28 14PR	TL	16.9	55.5	156	A8	32	R-4	8800	43	165.7	25.0
	1946301062	16.9-30 16PR	TL	16.5	57.7	156	A8	32	R-4	8800	47	172.6	26.1