

IND80

EM / INDUSTRIAL TYRES

IND80	Product Code	Tyre Size & Ply Rating	TT/ TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	TRA Code	Load & Pressure		Dynamic Rolling Circumference	Static Loaded Radius
				Section Width	Overall Diameter				Tyre Load Capacity	Tyre Pressure At Max. Load		
				mm	mm				kg	psi		
	U6161242OZK	10-16.5 12PR	TL	256	793	138	A3	R-4	2360	84	2374	359
	U6162252OZK	12-16.5 14PR	TL	297	858	148	A3	R-4	3150	90	2558	385
	U6181042OZK	10.5/80-18 12PR	TL	271	892	135	A8	R-4	2180	62	2666	403
	U6182152OZK	12.5/80-18 14PR	TL	285	955	146	A8	R-4	3000	62	2844	428
	U6207062OZK	16.0/70-20 16PR	TL	385	1091	166	A2	R-4	5300	65	3244	487
	U6207162OZK	405/70-20 16PR	TL	385	1091	166	A2	R-4	5300	65	3244	487
	U6243062OZK	15.5/80-24 16PR	TL	412	1269	162	A8	R-4	4750	72	3780	569
	U6245062OZK	16.0/70-24 16PR	TL	418	1200	169	A2	R-4	5800	65	3584	541
	U6245162OZK	405/70-24 16PR	TL	418	1200	169	A2	R-4	5800	65	3584	541
	U6246062OZK	16.9-24 16PR	TL	429	1310	154	A8	R-4	3750	46	3895	585
	U6246162OZK	440/80-24 16PR	TL	429	1310	154	A8	R-4	3750	46	3895	585
	U6247052OZK	17.5L-24 14PR	TL	475	1277	154	A8	R-4	3750	46	3802	572
	U6248052OZK	19.5L-24 14PR	TL	495	1314	154	A8	R-4	3750	38	3907	587
	U6251052OZK	15.5-25 14PR	TL	400	1286	173	A2	R-4	6500	68	3836	578
	U6261052OZK	18.4-26 14PR	TL	467	1425	160	A8	R-4	4500	42	4237	636
	U6281052OZK	16.9-28 14PR	TL	429	1410	156	A8	R-4	4000	43	4210	635
	U6281152OZK	440/80-28 14PR	TL	429	1410	156	A8	R-4	4000	43	4210	635
	U6301062OZK	16.9-30 16PR	TL	418	1466	156	A8	R-4	4000	47	4384	663