

Product Code	Tire Size & Ply Rating	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth	TRA Code	Load & Pressure		Dynamic Rolling Circumference	Static Loaded Radius
			Section Width	Overall Diameter					Tire Load Capacity	Tire Pressure At Max. Load		
			32nds									
1945241011	8.3-24 6PR	TT	8.3	39.7	105	A6	28	R-1	2040	30	119.8	18.3
1945241021	8.3-24 8PR	TT	8.3	39.7	108	A6	28	R-1	2200	35	119.8	18.3
1945242011	9.50-24 6PR	TT	9.5	41.3	110	A6	35	R-1	2340	26	124.4	18.9
1945242021	9.50-24 8PR	TT	9.5	41.3	116	A6	35	R-1	2760	34	124.4	18.9
1945243011	11.2-24 6PR	TT	11.2	43.5	110	A6	40	R-1	2340	26	130.6	19.8
1945243021	11.2-24 8PR	TT	11.2	43.5	116	A6	40	R-1	2760	34	130.6	19.8
1945243041	11.2-24 12PR	TT	11.2	43.5	122	A6	40	R-1	3300	40	130.6	19.8
1945244011	12.4-24 6PR	TT	12.4	45.7	115	A6	40	R-1	2680	24	136.7	20.7
1945244021	12.4-24 8PR	TT	12.4	45.7	118	A6	40	R-1	2910	29	136.7	20.7
1945244041	12.4-24 12PR	TT	12.4	45.7	124	A6	40	R-1	3520	35	136.7	20.7
1945245011	13.6-24 6PR	TT	13.6	47.6	120	A6	42	R-1	3080	22	142.2	21.5
1945245021	13.6-24 8PR	TT	13.6	47.6	123	A6	42	R-1	3420	28	142.2	21.5
1945245041	13.6-24 12PR	TT	13.6	47.6	129	A6	42	R-1	4080	34	142.2	21.5
1945246011	14.9-24 6PR	TT	14.9	49.8	125	A6	40	R-1	3640	20	148.3	22.3
1945246021	14.9-24 8PR	TT	14.9	49.8	128	A6	40	R-1	3960	26	148.3	22.3
1945246031	14.9-24 10PR	TT	14.9	49.8	131	A6	40	R-1	4300	30	148.3	22.3
1945246051	14.9-24 14PR	TT	14.9	49.8	137	A6	40	R-1	5080	38	148.3	22.3
1945248021	16.9-24 8PR	TT	16.9	52.6	133	A6	40	R-1	4540	25	156.1	23.4
1945248031	16.9-24 10PR	TT	16.9	52.6	136	A6	40	R-1	4940	29	156.1	23.4
1945248051	16.9-24 14PR	TT	16.9	52.6	141	A6	40	R-1	5680	35	156.1	23.4
1945247042	15.5/80-24 12PR	TL	15.5	49.6	157	A6	40	R-1	9100	44	147.8	22.2
1945247062	15.5/80-24 16PR	TL	15.5	49.6	163	A6	40	R-1	10700	58	147.8	22.2
1945261031	14.9-26 10PR	TT	14.9	51.8	133	A6	40	R-1	4540	30	154.6	23.3
1945262031	18.4-26 10PR	TT	18.4	57.5	142	A6	43	R-1	5840	26	170.8	25.6
1945262061	18.4-26 16PR	TT	18.4	57.5	153	A6	43	R-1	8050	44	170.8	25.6
1945261051	14.9-26 14PR	TT	14.9	51.8	140	A6	40	R-1	5520	39	154.6	23.3
1945281011	11.2-28 6PR	TT	11.2	47.4	112	A6	42	R-1	2470	26	142.9	21.8
1945281021	11.2-28 8PR	TT	11.2	47.4	118	A6	42	R-1	2910	34	142.9	21.8
1945282011	12.4-28 6PR	TT	12.4	49.6	117	A6	39	R-1	2830	25	149.0	22.6
1945282021	12.4-28 8PR	TT	12.4	49.6	125	A6	39	R-1	3640	30	149.0	22.6
1945283011	13.6-28 6PR	TT	13.6	51.6	121	A6	42	R-1	3200	23	154.6	23.4
1945283021	13.6-28 8PR	TT	13.6	51.6	125	A6	42	R-1	3640	29	154.6	23.4
1945284011	14.9-28 6PR	TT	14.9	53.7	125	A6	39	R-1	3640	20	160.7	24.3
1945284021	14.9-28 8PR	TT	14.9	53.7	130	A6	39	R-1	4180	26	160.7	24.3
1945284051	14.9-28 14PR	TT	14.9	53.7	143	A6	39	R-1	6000	40	160.7	24.3
1945285021	16.9-28 8PR	TT	16.9	56.5	135	A6	44	R-1	4800	24	168.5	25.4
1945285031	16.9-28 10PR	TT	16.9	56.5	139	A6	44	R-1	5360	29	168.5	25.4
1945285051	16.9-28 14PR	TT	16.9	56.5	143	A6	44	R-1	6000	34	168.5	25.4
1945301021	14.9-30 8PR	TT	14.9	55.7	132	A6	43	R-1	4400	26	166.9	25.3
1945301031	14.9-30 10PR	TT	14.9	55.7	136	A6	43	R-1	4940	29	166.9	25.3
1945302021	16.9-30 8PR	TT	16.9	58.5	137	A6	44	R-1	5080	25	174.7	26.4
1945302031	16.9-30 10PR	TT	16.9	58.5	144	A6	44	R-1	6150	28	174.7	26.4
1945302051	16.9-30 14PR	TT	16.9	58.5	150	A6	44	R-1	7400	34	174.7	26.4
1945303021	18.4-30 8PR	TT	18.4	61.0	139	A6	43	R-1	5360	20	182.0	27.4
1945303031	18.4-30 10PR	TT	18.4	61.0	145	A6	43	R-1	6400	26	182.0	27.4
1945303051	18.4-30 14PR	TT	18.4	61.0	154	A6	43	R-1	8250	40	182.0	27.4
1945321021	8.3-32 8PR	TT	8.3	47.0	111	A6	34	??	2400	46	143.1	22.0
1945322021	9.5-32 8PR	TT	9.5	49.2	115	A6	38	R-1	2680	39	149.2	22.9
1945323021	12.4-32 8PR	TT	12.4	53.5	125	A6	40	R-1	3640	32	161.5	24.6
1945341031	16.9-34 10PR	TT	16.9	62.4	142	A6	43	R-1	5840	29	187.1	28.3
1945341051	16.9-34 14PR	TT	16.9	62.4	148	A6	43	R-1	6950	37	187.1	28.3
1945342031	18.4-34 10PR	TT	18.4	65.0	146	A6	43	R-1	6600	26	194.4	29.4
1945342051	18.4-34 14PR	TT	18.4	65.0	155	A6	43	R-1	8550	40	194.4	29.4
1945361011	12.4-36 6PR	TT	12.4	57.7	121	A6	40	R-1	3200	24	174.4	26.7
1945361021	12.4-36 8PR	TT	12.4	57.7	126	A6	40	R-1	3740	29	174.4	26.7
1945362011	13.6-36 6PR	TT	13.6	59.6	125	A6	40	R-1	3640	23	180.0	27.4
1945362021	13.6-36 8PR	TT	13.6	59.6	129	A6	40	R-1	4080	29	180.0	27.4
1945381021	12.4-38 8PR	TT	12.4	59.6	127	A6	40	R-1	3860	29	180.6	27.7
1945382021	13.6-38 8PR	TT	13.6	61.6	131	A6	42	R-1	4300	29	186.1	28.5
1945382031	13.6-38 10PR	TT	13.6	61.6	135	A6	42	R-1	4800	33	186.1	28.5
1945383021	14.00-38 8PR	TT	13.6	61.6	131	A6	42	R-1	4300	29	186.1	28.5
1945383031	14.00-38 10PR	TT	13.6	61.6	135	A6	42	R-1	4800	33	186.1	28.5
1945384031	15.5-38 10PR	TT	15.5	61.8	138	A6	43	R-1	5200	33	186.7	28.5
1945384041	15.5-38 12PR	TT	15.5	61.8	141	A6	43	R-1	5680	38	186.7	28.5
1945385031	16.9-38 10PR	TT	16.9	66.3	145	A6	44	R-1	6400	30	199.5	30.4
1945385051	16.9-38 14PR	TT	16.9	66.3	152	A6	44	R-1	7850	40	199.5	30.4
1945386031	18.4-38 10PR	TT	18.4	68.9	147	A6	44	R-1	6800	26	206.7	31.4
1945386051	18.4-38 14PR	TT	18.4	68.9	154	A6	44	R-1	8250	36	206.7	31.4